

46825 - UHU emaille 23g Bl. D

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version number 5 Revision: 12.02.2021 SECTION 1: Identification of the substance/mixture and of the company/ undertaking · 1.1 Product identifier · Trade name: UHU emaille 23g Bl. D 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Adhesive · 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 Fax: 0049-(0)7223-284-245 emaill: sds@boltonadhesives.com · Further information obtainable from: UHU QESH · 1.4 Emergency telephone number: Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40 England and Wales (NHS Direct) 111 Schottland (NHS 24) 111 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling: n-butyl acetate

(Contd. on page 2) EU-EN



Printing date 12.02.2021

Version number 5

Revision: 12.02.2021

(Contd. of page 1)

Trade name: UHU emaille 23g Bl. D

Hazard statements

- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P501 Dispose of contents/container in accordance with national regulations.

Additional information:

- EUH066 Repeated exposure may cause skin dryness or cracking.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:

Dangerous components.		
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-21194663267-34	2-methoxy-1-methylethyl acetate	2.5-10%
Additional information, For	the wording of the listed bezord phrases refer to eastion 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: No special measures required.

• After inhalation:

- Supply fresh air; consult doctor in case of complaints.
- No special measures required.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

EU-EN

(Contd. on page 3)



Printing date 12.02.2021

Version number 5

Revision: 12.02.2021

Trade name: UHU emaille 23g Bl. D

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 12.02.2021

Version number 5

Revision: 12.02.2021

Trade name: UHU emaille 23g Bl. D

(Contd. of page 3)

123-86-4 n-b	utyl acetate	
	-term value: 723 mg/m ³ , 150 ppm	
Long	term value: 241 mg/m³, 50 ppm	
108-65-6 2-m	ethoxy-1-methylethyl acetate	
	-term value: 550 mg/m³, 100 ppm -term value: 275 mg/m³, 50 ppm	
DNELs		
123-86-4 n-b	utyl acetate	
	onsumer, oral, longterm exposition	3.4 mg/kg bw/day
	onsumer, dermal, longterm exposition	3.4 mg/kg bw/day
	onsumer, inhalation, longterm exposition	
PNECs		····
123-86-4 n-b Fresh water	•	
	-	
Marine water		
Soil	0.0903 mg/kg formation: The lists valid during the ma	
General prot	e controls otective equipment: ective and hygienic measures:	to when handling chemicale
General prot The usual prot Wash hands Do not inhale Respiratory Protection o The glove m preparation.	ective equipment: ective and hygienic measures: ecautionary measures are to be adhered before breaks and at the end of work. gases / fumes / aerosols. protection: Not required. f hands: laterial has to be impermeable and r	esistant to the product/ the substance/ th
General prot The usual prot Wash hands Do not inhale Respiratory Protection o The glove m preparation. Selection of t degradation Material of g	ective equipment: ective and hygienic measures: ecautionary measures are to be adhered before breaks and at the end of work. gases / fumes / aerosols. protection: Not required. f hands: laterial has to be impermeable and r he glove material on consideration of th loves	esistant to the product/ the substance/ th
General prot The usual prot Wash hands Do not inhale Respiratory Protection o The glove m preparation. Selection of t degradation Material of g Recommendo glove materia	ective equipment: ective and hygienic measures: ecautionary measures are to be adhered before breaks and at the end of work. gases / fumes / aerosols. protection: Not required. f hands: naterial has to be impermeable and r he glove material on consideration of th loves ed thickness of the material: > 0,12 mm il: butyl rubber	
 General prof The usual prof Wash hands Do not inhale Respiratory Protection o The glove m preparation. Selection of t degradation Material of g Recommende glove materia thickness of t breakthrough The selection of quality and substances, 	betective equipment: ective and hygienic measures: ecautionary measures are to be adhered before breaks and at the end of work. gases / fumes / aerosols. protection: Not required. f hands: laterial has to be impermeable and r he glove material on consideration of th loves ed thickness of the material: > 0,12 mm it: butyl rubber he glove material: 0,6 - 0,8 mm time (maximum wearing time): 60 - 120 of the suitable gloves does not only dep I varies from manufacturer to manufactu the resistance of the glove material e checked prior to the application.	esistant to the product/ the substance/ the substance/ the penetration times, rates of diffusion and t

(Contd. on page 5)

EU-EN



Printing date 12.02.2021

Version number 5

Revision: 12.02.2021

(Contd. of page 4)

Trade name: UHU emaille 23g Bl. D

· Eye protection:

Tightly sealed goggles

Goggles recommended during refilling

· 9.1 Information on basic physical and chemical properties			
General Information Appearance: Form:	Fluid		
Colour: Odour:	White Characteristic		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. 124-128 °C		
Flash point:	27 °C		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	315 °C		
Decomposition temperature:	Not determined.		
Auto-ignition temperature:	Product is not selfigniting.		
Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.		
Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %		
Vapour pressure at 20 °C:	10.7 hPa		
Density at 20 °C: Relative density Vapour density Evaporation rate	0.896 g/cm ³ Not determined. Not determined. Not determined.		
Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
Partition coefficient: n-octanol/water:	Not determined.		
Viscosity: Dynamic at 20 °C: Kinematic:	2500 mPas Not determined.		

www.uhu.com

EU-EN



Printing date 12.02.2021

Version number 5

Revision: 12.02.2021

Trade name: UHU emaille 23g Bl. D

(Contd. of p	
Solvent content:	54.0.%
Organic solvents:	54.0 %
Solids content:	42.0 %
• 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13100 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)

Inhalative LC50/4 h >21 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8532 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Not applicable.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.

• **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 12.02.2021

Version number 5

Revision: 12.02.2021

(Contd. of page 6)

Trade name: UHU emaille 23g Bl. D

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR/ADN, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR/ADN	1263 PAINT	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es)		
ADR/ADN		
Class	3 (F1) Flammable liquids.	



Printing date 12.02.2021	Version number 5	Revision: 12.02.2021
Trade name: UHU emaille 23g Bl. D		
		(Contd. of page 7)
·Label	3	
· Class	3 Flammable liquid	S.
· Label	3	
 14.4 Packing group ADR/ADN, IMDG, IATA 	Ш	
• 14.5 Environmental hazards:	Not applicable.	
 · 14.6 Special precautions for user · Hazard identification number (Kem · EMS Number: 	Warning: Flammab nler code): 30 F-E,S-D	le liquids.
 14.7 Transport in bulk according to of Marpol and the IBC Code 	o Annex II Not applicable.	
 Transport/Additional information: Quantity limitations 	On passenger aircr On cargo aircraft or	
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) 		tity per inner packaging: 30 ml tity per outer packaging: 1000
 Transport category Tunnel restriction code 	3 D/E	
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 		tity per inner packaging: 30 ml tity per outer packaging: 1000
· UN "Model Regulation":	UN 1263 PAINT, 3,	III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $5000\ t$
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

(Contd. on page 9) EU-EN-

www.uhu.com



Printing date 12.02.2021

Version number 5

Revision: 12.02.2021

(Contd. of page 8)

Trade name: UHU emaille 23g Bl. D

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles		
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.		

Department issuing SDS: UHU QESH

· Contact: UHU QESH

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered.

EU-EN